

# ALLE MODELLE IM ÜBERBLICK



**MHS**  
SCHNEIDETECHNIK GMBH

	PCE 70-21 KS	PCE 100-21 KS	PCE 70-25 KS	PCE 100-25 KS	PCE 70-36 KS	PCE 70-21 ES	PCE 100-21 ES	PCE 70-25 ES	PCE 100-25 ES	PCE 70-36 ES	PCE 65 T
Max. Einlegelänge mm	750	1050	700	1100	700	700	1000	700	1100	700	650
Einlegequerschnitt mm (BxH)	210 x 230	210 x 230	250 x 240	250 x 240	360 x 220	210 x 230	210 x 230	250 x 240	250 x 240	360 x 220	180 x 170
Außenmaße mm (LxBxH) (L mit Band)	1845 x 830 x 1230 (2912)	2495 x 830 x 1230 (3312)	1925 x 950 x 1335 (2990)	2725 x 950 x 1335 (3390)	1925 x 1175 x 1450 (2990)	1845 x 830 x 1387 (2912)	2495 x 830 x 1387 (3312)	1925 x 950 x 1420 (2990)	2725 x 950 x 1420 (3390)	1925 x 1175 x 1450 (2990)	1560 x 670 x 670
Anschlusswerte (andere Spannung nach Vorgabe)	400 V / 2,7 kW	400 V / 2,7 kW	400 V / 4,5 kW	400 V / 4,5 kW	400 V / 4,5 kW	400 V / 2,7 kW	400 V / 2,7 kW	400 V / 4,5 kW	400 V / 4,5 kW	400 V / 4,5 kW	400 V / 2,7 kW
Gewicht kg	240	260	450	500	500	240	260	450	500	500	200
Leistung Einzelmesser Abschnitte/Minute	220	220	220	220	220	220	220	220	220	220	180
Leistung Doppelmesser Abschnitte/Minute (kontinuierlich)	440	440	440	440	–	440	440	440	440	–	–
Scheibenstärke mm	1 - 32	1 - 32	1 - 32	1 - 32	1 - 32	1 - 700	1 - 1000	1 - 700	1 - 1000	1 - 700	1 - 32
Scheibenstärke optional	1 - 50	1 - 50	1 - 50	1 - 50	1 - 50	–	–	–	–	–	–
<b>FUNKTIONEN</b>											
Anfahreinrichtung	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Klappenstart	–	–	–	–	–	✓	✓	✓	✓	✓	–
Rückfahrwegbegrenzung	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Restscheibenaufteilung	–	–	–	–	–	✓	✓	✓	✓	✓	–
Schneidsoftware	–	–	–	–	–	✓	✓	✓	✓	✓	–
Verstärkter Antrieb	–	–	✓	✓	–	–	–	✓	✓	–	–
Transportband	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	–
Verstellbarer Greifer	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	–

✓ standard

✓ optional