


ALL MODELS AT A GLANCE



	PCE 70-21 KS	PCE 100-21 KS	PCE 70-25 KS	PCE 100-25 KS	PCE 70-36 KS	PCE 70-21 ES	PCE 100-21 ES	PCE 70-25 ES	PCE 100-25 ES	PCE 70-36 ES	PCE 65 T
Max. input length mm	750	1050	700	1100	700	700	1000	700	1100	700	650
Cross section mm (W x H)	210 x 230	210 x 230	250 x 240	250 x 240	360 x 220	210 x 230	210 x 230	250 x 240	250 x 240	360 x 220	180 x 170
Outer dimensions mm (L x W x H) (L with belt)	1845 x 830 x 1230 (2912)	2495 x 830 x 1230 (3312)	1925 x 950 x 1335 (2990)	2725 x 950 x 1335 (3390)	1925 x 1175 x 1450 (2990)	1845 x 830 x 1387 (2912)	2495 x 830 x 1387 (3312)	1925 x 950 x 1420 (2990)	2725 x 950 x 1420 (3390)	1925 x 1175 x 1450 (2990)	1560 x 670 x 670
Connection (other voltages on request)	400 V / 2.7 kW	400 V / 2.7 kW	400 V / 4.5 kW	400 V / 4.5 kW	400 V / 4.5 kW	400 V / 2.7 kW	400 V / 2.7 kW	400 V / 4.5 kW	400 V / 4.5 kW	400 V / 4.5 kW	400 V / 2.7 kW
Weight kg	240	260	450	500	500	240	260	450	500	500	200
Single blade performance slices/minute	220	220	220	220	220	220	220	220	220	220	180
Double blade performance slices/minute (continuous)	440	440	440	440	-	440	440	440	440	-	-
Slice thickness mm	1-32	1-32	1-32	1-32	1-32	1-750	1-1000	1-700	1-1000	1-700	1-32
Slice thickness optional	1-50	1-50	1-50	1-50	1-50	-	-	-	-	-	-
FUNCTIONS											
Startup system	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Flap start	-	-	-	-	-	✓	✓	✓	✓	✓	-
Return limiter	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Distribution of remaining slice	-	-	-	-	-	✓	✓	✓	✓	✓	-
Slicing software	-	-	-	-	-	✓	✓	✓	✓	✓	-
Reinforced drive	-	-	✓	✓	-	-	-	✓	✓	-	-
Conveyor belt	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-
Adjustable gripper	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	-