









































ALL PCE MODELS AT A GLANCE

 as standard  optional



	PCE 65 T	PCE 70-21 KS	PCE 100-21 KS	PCE 70-25 KS	PCE 100-25 KS	PCE 70-36 KS	PCE 70-21 ES	PCE 100-21 ES	PCE 70-25 ES	PCE 100-25 ES	PCE 70-36 ES
Max. input length mm	650	750	1050	700	1100	700	750	1050	700	1100	700
Cross section mm (WxH)	180 x 170	210 x 230	210 x 230	250 x 240	250 x 240	360 x 220	210 x 230	210 x 230	250 x 240	250 x 240	360 x 220
Outer dimensions mm (LxWxH) (L with belt)	1560 x 670 x 670	1845 x 830 x 1230 (2912)	2495 x 830 x 1230 (3312)	1925 x 950 x 1335 (2990)	2725 x 950 x 1335 (3390)	1925 x 1175 x 1450 (2990)	1900 x 827 x 1292 (2967)	1845 x 830 x 1230 (2912)	2495 x 830 x 1230 (3312)	1925 x 950 x 1335 (2990)	2725 x 950 x 1335 (3390)
Connection (with belt)	3Ph + PE 400V 50 Hz 2.7 kW	3Ph + PE 400V 50 Hz 2.7 kW (3.2 kW)	3Ph + PE 400V 50 Hz 2.7 kW (3.2 kW)	3Ph + PE 400V 50 Hz 4.5 kW (5.0 kW)	3Ph + PE 400V 50 Hz 4.5 kW (5.0 kW)	3Ph + PE 400V 50 Hz 4.5 kW (5.0 kW)	3Ph + N + PE 400V 50 Hz 2.7 kW (3.2 kW)	3Ph + N + PE 400V 50 Hz 2.7 kW (3.2 kW)	3Ph + N + PE 400V 50 Hz 4.5 kW (5.0 kW)	3Ph + N + PE 400V 50 Hz 4.5 kW (5.0 kW)	3Ph + N + PE 400V 50 Hz 4.5 kW (5.0 kW)
Weight kg	200	240	260	450	500	500	240	260	450	500	500
Single blade performance slices/minute	180	220	220	220	220	220	220	220	220	220	220
Double blade performance slices/minute (continuous)	–	440	440	440	440	440	440	440	440	440	440
Slice thickness mm	1 – 32	1 – 32	1 – 32	1 – 32	1 – 32	1 – 32	0.5 – 500	0.5 – 500	0.5 – 500	0.5 – 500	0.5 – 500
Slice thickness optional	–	1 – 50	1 – 50	1 – 50	1 – 50	1 – 50	–	–	–	–	–
Functions											
Startup system											
Flap start	–	–	–	–	–	–					
Return limiter											
Distribution of remaining slice	–	–	–	–	–	–					
Section software	–	–	–	–	–	–					
Reinforced drive	–					–					–
Conveyor belt	–										
Adjustable gripper	–		